PERISTALTIC SYSTEM DOSING PUMP
KemiDose Series

The **KemiDose** Display is a professional pump suitable for use in water treatment markets.



FEATURES:

- IP 65 Level Protection
- Alphanumeric Display
- Wheel holder mounted on ball bearing, for a longer pump life
- New motors with extended life time
- Snap on transparent cover
- Two roller PTFE body, for a more proportional dosing and an extended lifetime

TECHNICALCHARACTERISTICS:

- **FLOW RATES**
  - 25mL/H;
  - 151 mL/H,
  - 1510 mL/H,
  - 5 L/H,
  - 9 L/H.
- **BACK PRESSURE**
  - 1,5 bar
- **POWER SUPPLY**
  - 230÷Vac - 50/60 Hz - 12,5 W with galvanized insulation
- **MATERIALS**
  - **ENCLOSURE**: ABS with fiber glass
  - **PUMP HEAD**: PP
  - **TUBES**: Santoprene
- **DOSING**
  - proportional mode
- **MOTORS**
  - Brushed DC Motors
- **MEASURE**
  - Frequency input
  - Weekly timer
- **FUNCTIONS**
  - Proportional dosing by pH feedback measure

PUMP KEY CODE

1	Pool Series						
	2	Model: One, Dose, Master					
		3-4	Measure: TM= Weekly Timer, PG= Proportional				
			5-6	Pressure: 0H=0,5 Bar, 1H= 1,5Bar, 20= 2 Bar			
				7-8	Flowrate: 0H=0,5 L/H, 1H= 1,5L7H, 20= 2 L/H		
					9	Power Supply: A= 220 Vac	
						10	Option
						11-12	Free
T	D	TM	1H	1H	A	0	00

DIMENSIONS

Single

